

Features

- Formerly a Riedon™ product
- Wirewound technology
- Power ratings from 60 to 500 watts
- Resistance range of 0.1 to 1K Ω
- Non-inductive winding available
- Tolerances of 1 %, 5 %, or 10 %
- Compact packaging
- RoHS compliant*

Applications

- Renewable energy
- Power converters
- Motor drives

BR / BRT Series – Riedon™ High Power Metal Clad Braking Resistors by Bourns

Electrical Characteristics

Bourns Part Number	Power Rating (W) ¹		Resistance Range (Ω)	
	Heat Sink	Free Air	Standard	Non-inductive
BR60 / BRT60	60	50	0.1 - 1K	10 - 100
BR80 / BRT80	80	64		
BR100 / BRT100	100	80		
BR120 / BRT120	120	96		
BR150 / BRT150	150	120		
BR200 / BRT200	200	140		
BR300 / BRT300	300	210		
BR400 / BRT400	400	240		
BR500 / BRT500	500	300		

Note:

1. Stated power rating is dependent on the resistor being mounted to a panel or heat sink of adequate mass to prevent the resistor surface from exceeding 250 °C. See temperature rise and derating curves for more information.

Environmental Specifications


Parameter	Specification
Operating Temperature Range	-55 °C to +200 °C
TCR	< ± 260 PPM/°C maximum
Dielectric Withstanding Voltage	2500 VAC
Insulation Resistance	20 M Ω minimum
Short Time Overload	± 2 % + 0.05 Ω - 10 times rated power for 5 seconds
Moisture Resistance	± 3 % + 0.05 Ω 40 °C, 95 % RH, 100 VDC case to terminal, 500 hours
Load Life	± 5 % + 0.05 Ω 90 minutes rated power, 30 minutes off, 500 hours
Thermal Shock	± 2 % + 0.05 Ω 30 minutes rated power, 15 minutes -25 °C
Vibration	± 1 % + 0.05 Ω 10 Hz - 55 Hz - 10 Hz (1 minute) 2 hours each direction
Moisture Load Life	± 3 % + 0.05 Ω 40 °C, 95 % RH, 90 minutes 10 % rated power, 30 minutes off 500 hours
Terminals	Standard: 6.35 mm (0.25 inch) fast-on, 0.8 mm (0.032 inch) thick. Optional: M4 tap or flying lead terminations (contact Bourns)

Additional Information

Click these links for more information:




How To Order



Typical Part Marking

Represents total content. Layout may vary.



WARNING Cancer and Reproductive Harm
www.P65Warnings.ca.gov

*RoHS Directive 2015/863, Mar 31, 2015 and Annex.

Specifications are subject to change without notice. Users should verify actual device performance in their specific applications. The products described herein and this document are subject to specific legal disclaimers as set forth on the last page of this document, and at www.bourns.com/docs/legal/disclaimer.pdf.

“Bourns” is a registered trademark of Bourns, Inc. in the United States and other countries.

In April 2023, BE Services Company, Inc., a subsidiary of Bourns, Inc., purchased certain assets of Riedon, Inc., including its logo and trademarks and the right to continue to manufacture former Riedon™ products.

“Riedon Logo” is a registered trademark of BE Services Company, Inc., in the United States.


“Riedon” is a trademark of BE Services Company, Inc.

BR/BRT Series – Riedon™ High Power Metal Clad Braking Resistors by Bourns



Product Dimensions

BR (flat) Series



Model	L1 ± 2.0 (0.78)	L2 ± 2.0 (0.78)	L3 ± 2.0 (0.78)	W ± 0.5 (0.020)	H ± 0.5 (0.020)	D ± 0.5 (0.020)	Mass/Weight (g)
BR60	$\frac{100}{(3.94)}$	$\frac{87}{(3.43)}$	$\frac{60}{(2.36)}$	41 (1.61)	22 (0.87)	4.3 (0.17)	125
BR80	$\frac{150}{(5.91)}$	$\frac{137}{(5.39)}$	$\frac{110}{(4.33)}$				200
BR100	$\frac{165}{(6.49)}$	$\frac{152}{(5.98)}$	$\frac{125}{(4.92)}$				240
BR120	$\frac{182}{(7.17)}$	$\frac{169}{(6.65)}$	$\frac{142}{(5.59)}$				270
BR150	$\frac{210}{(8.27)}$	$\frac{197}{(7.76)}$	$\frac{170}{(6.69)}$				340
BR200	$\frac{165}{(6.49)}$	$\frac{146}{(5.75)}$	$\frac{125}{(4.92)}$	60 (2.36)	30 (1.18)	5.3 0.21	450
BR300	$\frac{215}{(8.46)}$	$\frac{196}{(7.72)}$	$\frac{175}{(6.89)}$				610
BR400	$\frac{265}{(10.43)}$	$\frac{246}{(9.69)}$	$\frac{225}{(8.86)}$				870
BR500	$\frac{335}{(13.19)}$	$\frac{316}{(12.44)}$	$\frac{295}{(11.62)}$				950

Specifications are subject to change without notice.

Users should verify actual device performance in their specific applications.


The products described herein and this document are subject to specific legal disclaimers as set forth on the last page of this document, and at www.bourns.com/docs/legal/disclaimer.pdf.

BR/BRT Series – Riedon™ High Power Metal Clad Braking Resistors by Bourns



Product Dimensions

BRT (tall) Series



Terminals = 6.35 mm
(0.25 inch) fast-on

DIMENSIONS: $\frac{\text{MM}}{\text{(INCHES)}}$

Model	L1 ± 2.0 (0.78)	L2 ± 2.0 (0.78)	L3 ± 2.0 (0.78)	W ± 0.5 (0.020)	H ± 0.5 (0.020)	D ± 0.5 (0.020)	O1 ± 0.5 (0.020)	O2 ± 0.5 (0.020)	Mass/Weight (g)
BRT60	$\frac{100}{(3.94)}$	$\frac{87}{(3.43)}$	$\frac{60}{(2.36)}$	$\frac{41}{(1.61)}$	$\frac{22}{(0.87)}$	$\frac{4.3}{(0.17)}$	$\frac{7.8}{(0.31)}$	$\frac{10.0}{(0.39)}$	125
BRT80	$\frac{150}{(5.91)}$	$\frac{137}{(5.39)}$	$\frac{110}{(4.33)}$						200
BRT100	$\frac{165}{(6.49)}$	$\frac{152}{(5.98)}$	$\frac{125}{(4.92)}$						240
BRT120	$\frac{182}{(7.17)}$	$\frac{169}{(6.65)}$	$\frac{142}{(5.59)}$						270
BRT150	$\frac{210}{(8.27)}$	$\frac{197}{(7.76)}$	$\frac{170}{(6.69)}$						340
BRT200	$\frac{165}{(6.49)}$	$\frac{146}{(5.75)}$	$\frac{125}{(4.92)}$	$\frac{60}{(2.36)}$	$\frac{30}{(1.18)}$	$\frac{5.3}{0.21}$	$\frac{10.4}{(0.41)}$	$\frac{14.6}{(0.57)}$	450
BRT300	$\frac{215}{(8.46)}$	$\frac{196}{(7.72)}$	$\frac{175}{(6.89)}$						610
BRT400	$\frac{265}{(10.43)}$	$\frac{246}{(9.69)}$	$\frac{225}{(8.86)}$						870
BRT500	$\frac{335}{(13.19)}$	$\frac{316}{(12.44)}$	$\frac{295}{(11.62)}$						950

Specifications are subject to change without notice.


Users should verify actual device performance in their specific applications.

The products described herein and this document are subject to specific legal disclaimers as set forth on the last page of this document, and at www.bourns.com/docs/legal/disclaimer.pdf.

BR/BRT Series – Riedon™ High Power Metal Clad Braking Resistors by Bourns



Power Derating



Packaging Specifications

Bulk..... 10 pcs. per box



Americas: Tel: +1 951-781-5500 • Email: americus@bourns.com
Mexico: Tel: +52-614-478-0400 • Email: mexicus@bourns.com
Asia: Tel: +886-2-2562-4117 • Email: asiacus@bourns.com
EMEA: Tel: +36 88 885 877 • Email: eurocus@bourns.com
www.bourns.com

REV. 11/24

Specifications are subject to change without notice.

Users should verify actual device performance in their specific applications.

The products described herein and this document are subject to specific legal disclaimers as set forth on the last page of this document, and at www.bourns.com/docs/legal/disclaimer.pdf.

This legal disclaimer applies to purchasers and users of Bourns® products manufactured by or on behalf of Bourns, Inc. and its affiliates (collectively, "Bourns").

Unless otherwise expressly indicated in writing, Bourns® products and data sheets relating thereto are subject to change without notice. Users should check for and obtain the latest relevant information and verify that such information is current and complete before placing orders for Bourns® products.

The characteristics and parameters of a Bourns® product set forth in its data sheet are based on laboratory conditions, and statements regarding the suitability of products for certain types of applications are based on Bourns' knowledge of typical requirements in generic applications. The characteristics and parameters of a Bourns® product in a user application may vary from the data sheet characteristics and parameters due to (i) the combination of the Bourns® product with other components in the user's application, or (ii) the environment of the user application itself. The characteristics and parameters of a Bourns® product also can and do vary in different applications and actual performance may vary over time. Users should always verify the actual performance of the Bourns® product in their specific devices and applications, and make their own independent judgments regarding the amount of additional test margin to design into their device or application to compensate for differences between laboratory and real world conditions.

Unless Bourns has explicitly designated an individual Bourns® product as meeting the requirements of a particular industry standard (e.g., IATF 16949) or a particular qualification (e.g., UL listed or recognized), Bourns is not responsible for any failure of an individual Bourns® product to meet the requirements of such industry standard or particular qualification. Users of Bourns® products are responsible for ensuring compliance with safety-related requirements and standards applicable to their devices or applications.

Bourns® products are not recommended, authorized or intended for use in nuclear, lifesaving, life-critical or life-sustaining applications, nor in any other applications where failure or malfunction may result in personal injury, death, or severe property or environmental damage. Unless expressly and specifically approved in writing by two authorized Bourns representatives on a case-by-case basis, use of any Bourns® products in such unauthorized applications might not be safe and thus is at the user's sole risk. Life-critical applications include devices identified by the U.S. Food and Drug Administration as Class III devices and generally equivalent classifications outside of the United States.

Bourns expressly identifies those Bourns® standard products that are suitable for use in automotive applications on such products' data sheets in the section entitled "Applications." Unless expressly and specifically approved in writing by two authorized Bourns representatives on a case-by-case basis, use of any other Bourns® standard products in an automotive application might not be safe and thus is not recommended, authorized or intended and is at the user's sole risk. If Bourns expressly identifies a sub-category of automotive application in the data sheet for its standard products (such as infotainment or lighting), such identification means that Bourns has reviewed its standard product and has determined that if such Bourns® standard product is considered for potential use in automotive applications, it should only be used in such sub-category of automotive applications. Any reference to Bourns® standard product in the data sheet as compliant with the AEC-Q standard or "automotive grade" does not by itself mean that Bourns has approved such product for use in an automotive application.

Bourns® standard products are not tested to comply with United States Federal Aviation Administration standards generally or any other generally equivalent governmental organization standard applicable to products designed or manufactured for use in aircraft or space applications. Bourns expressly identifies Bourns® standard products that are suitable for use in aircraft or space applications on such products' data sheets in the section entitled "Applications." Unless expressly and specifically approved in writing by two authorized Bourns representatives on a case-by-case basis, use of any other Bourns® standard product in an aircraft or space application might not be safe and thus is not recommended, authorized or intended and is at the user's sole risk.

The use and level of testing applicable to Bourns® custom products shall be negotiated on a case-by-case basis by Bourns and the user for which such Bourns® custom products are specially designed. Absent a written agreement between Bourns and the user regarding the use and level of such testing, the above provisions applicable to Bourns® standard products shall also apply to such Bourns® custom products.

Users shall not sell, transfer, export or re-export any Bourns® products or technology for use in activities which involve the design, development, production, use or stockpiling of nuclear, chemical or biological weapons or missiles, nor shall they use Bourns® products or technology in any facility which engages in activities relating to such devices. The foregoing restrictions apply to all uses and applications that violate national or international prohibitions, including embargos or international regulations. Further, Bourns® products and Bourns technology and technical data may not under any circumstance be exported or re-exported to countries subject to international sanctions or embargoes. Bourns® products may not, without prior authorization from Bourns and/or the U.S. Government, be resold, transferred, or re-exported to any party not eligible to receive U.S. commodities, software, and technical data.

To the maximum extent permitted by applicable law, Bourns disclaims (i) any and all liability for special, punitive, consequential, incidental or indirect damages or lost revenues or lost profits, and (ii) any and all implied warranties, including implied warranties of fitness for particular purpose, non-infringement and merchantability.

For your convenience, copies of this Legal Disclaimer Notice with German, Spanish, Japanese, Traditional Chinese and Simplified Chinese bilingual versions are available at:

Web Page: <http://www.bourns.com/legal/disclaimers-terms-and-policies>

PDF: <http://www.bourns.com/docs/Legal/disclaimer.pdf>