


MATERIAL DECLARATION SHEET



Material Number	SRR0805-series			
Product Line	SHIELDED SMD POWER INDUCTOR			
Compliance Date	2009.07.02			
RoHS Compliant	YES	MSL	1	

No.	Construction Element(subpart)	Homogeneous Material	Material weight [mg]	Homogeneous Material\ Substances	CASRN if applicable	Materials Mass %	Material Mass % of total unit wt.	Subpart mass of total wt. (%)
1	Ferrite Material	F4D	480	Iron oxide (Fe ₂ O ₃)	1309-37-1	60	40.8	68
				Nickel oxide (NiO)	1313-99-1	10	6.8	
				Zinc oxide (ZnO)	1314-13-2	20	13.6	
				Copper oxide (CuO)	1317-38-0	10	6.8	
2	Winding Wire	2SFBW	105	Copper (Cu)	7440-50-8	95	14.3	15
				Polyester Resin	N/A	5	0.7	
3	Solder	Lead free-solder	5	Tin (Sn)	7440-31-5	96.5	0.965	1
				Silver (Ag)	7440-22-4	3	0.03	
				Copper (Cu)	7440-50-8	0.5	0.005	
4	BASE	LCP-E4008	50	Aromatic polyester resin	6088-52-0	100	7	7
5	BASE Terminal Electrode	C5191/Sn/ Ni	15	Phosphor bronze	N/A	90	1.8	2
				Tin (Sn)	7440-31-5	7	0.14	
				Nickel (Ni)	7440-02-0	3	0.06	
6	GAP	LCP-E4008	25	Aromatic polyester resin	6088-52-0	100	4	4
7	Adhesive	6020H-2	20	Bisphenol A Epoxy Resin	25068-38-6	63	1.89	3
				Alkyd glycidyl ether	68609-97-2	3	0.09	
				Methyl imidazole	693-98-1	5	0.15	
				Carbon black	1333-86-4	3	0.09	
				Silicon dioxide	7631-86-9	26	0.78	

MATERIAL DECLARATION SHEET



Total weight	700
--------------	-----

This Document was updated on: 10-28-2010

Important remarks:

1. It is the responsibility of the user to verify they are accessing the latest version.