


MATERIAL DECLARATION SHEET



Material Number	SRR4011-series			
Product Line	SHIELDED SMD POWER INDUCTOR			
Compliance Date	2009.07.06			
RoHS Compliant	YES	MSL	1	

No.	Construction Element(subpart)	Homogeneous Material	Material weight [mg]	Homogeneous Material\ Substances	CASRN if applicable	Materials Mass %	Material Mass % of total unit wt.	Subpart mass of total wt. (%)
1	Ferrite Material	F5H	98	Iron oxide (Fe ₂ O ₃)	1309-37-1	60	46.2	77
				Nickel oxide (NiO)	1313-99-1	10	7.7	
				Zinc oxide (ZnO)	1314-13-2	20	15.4	
				Copper oxide(CuO)	1317-38-0	10	7.7	
2	Winding Wire	2SFBW	15	Copper (Cu)	7440-50-8	95	11.4	12
				Polyester Resin	N/A	5	0.6	
3	Solder	Lead free-solder	6	Tin Sn	7440-31-5	96.5	4.83	5
				Silver Ag	7440-22-4	3	0.15	
				Copper Cu	7440-50-8	0.5	0.02	
4	Terminal	Ag/Ni/Sn	5	Silver (Ag)	7440-22-4	46	1.84	4
				Nickel (Ni)	7440-02-0	18	0.72	
				Tin (Sn)	7440-31-5	36	1.44	

MATERIAL DECLARATION SHEET



5	Adhesive	6020H-6-3	3	Bisphenol A Epoxy Resin	25068-38-6	63	1.26	2
				Alkyd glycidyl ether	68609-97-2	3	0.06	
				Methyl imidazole	693-98-1	5	0.1	
				Carbon black	1333-86-4	3	0.06	
				Silicon dioxide	7631-86-9	26	0.52	
		Total weight	127					

This Document was updated on: 10-28-2010

Important remarks:

1. It is the responsibility of the user to verify they are accessing the latest version.