

Features

- Wide terminal type
- Excellent heat dissipation
- Low inductance <5 nH
- Low thermal EMF <40 $\mu\text{V}/^\circ\text{C}$
- High reliability
- AEC-Q200 compliant
- RoHS compliant* and halogen free**

Applications

- Current sensing
- Power supplies
- Stepper motor drives
- Input amplifiers

CRK Series Metal Strip, Wide Terminal Current Sense Resistor

Electrical Characteristics

Characteristic	Model		
	CRK0612	CRK0815	CRK1225
Power Rating @ 70 °C	1 W		3 W
Resistance Value	1 m Ω ~ 10 m Ω	1 m Ω ~ 30 m Ω	1 m Ω ~ 55 m Ω
Operation Temperature Range	-55 °C ~ +170 °C		
Temperature Coefficient of Resistance	± 100 PPM/°C		
Tolerance	± 1 %, 5 %		
Insulation Resistance	Over 100 M Ω		
Maximum Working Voltage (V)	$(P \cdot R)^{1/2}$		

Note: 1 Watts with total solder pad and trace size of 300 mm²

Additional Information

Click these links for more information:



Environmental Characteristics

Storage Conditions

Temperature +5 °C ~ +35 °C
 Humidity 40 % ~ 75 %

Shelf Life


..... 2 years from manufacturing date

Solder Recommendations

..... Reflow profile
 (Solder: Sn96.5 / Ag3 / Cu0.5)


Moisture Sensitivity Level 1

Product Dimensions



	W	L	D	t
CRK0612	3.20 ± 0.2 (.126 \pm .008)	1.70 ± 0.2 (.067 \pm .008)	0.40 ± 0.2 (.016 \pm .008)	0.60 ± 0.2 (.027 \pm .008)
CRK0815	3.75 ± 0.3 (.148 \pm .012)	2.30 ± 0.2 (.091 \pm .008)	0.50 ± 0.2 (.020 \pm .008)	0.70 ± 0.2 (.028 \pm .008)
CRK1225	6.40 ± 0.3 (.252 \pm .012)	3.20 ± 0.3 (.126 \pm .012)	0.50 ± 0.2 (.020 \pm .008)	0.90 ± 0.25 (.035 \pm .010)

Recommended Solder Pad Dimensions



	a	b	L
CRK0612	3.80 (0.15)	0.70 (0.03)	0.70 (0.03)
CRK0815	4.20 (0.17)	0.80 (0.03)	1.20 (0.05)
CRK1225	7.00 (0.27)	1.00 (0.04)	2.30 (0.09)



WARNING Cancer and Reproductive Harm - www.P65Warnings.ca.gov

* RoHS Directive 2015/863, Mar 31, 2015 and Annex.

** Bourns considers a product to be "halogen free" if (a) the Bromine (Br) content is 900 ppm or less; (b) the Chlorine (Cl) content is 900 ppm or less; and (c) the total Bromine (Br) and Chlorine (Cl) content is 1500 ppm or less.

Specifications are subject to change without notice.

Users should verify actual device performance in their specific applications.

The products described herein and this document are subject to specific legal disclaimers as set forth on the last page of this document, and at www.bourns.com/docs/legal/disclaimer.pdf.

CRK Series Metal Strip, Wide Terminal Current Sense Resistor



Reliability Tests

Test Items	Reference Standard	Condition of Test	Test Limits
Temperature Coefficient of Resistance	IEC 60115-1-4.8 JIS-C5201-4.8	+25 °C ~ +125 °C	±100 PPM/°C
Operation Life	AEC-Q200 Test 8 MIL-STD-202 Method 108	1000 hours at TA=70 °C at 100 % rated power ON/OFF	< ±1 %
Short Time Overload	IEC 60115-1-4.13 JIS-C5201-4.13	5 X rated power for 5 sec.	< ±0.5 %
Biased Humidity	AEC-Q200 Test 7 MIL-STD-202 Method 103	85 °C, 85 % RH, 1000 hrs with 10 % rated power	< ±0.5 %
Temperature Cycle	AEC-Q200 Test 4 JESD22-A104	-55 °C & +155 °C, 1000 cycles	< ±0.5 %
Resistance to Soldering Heat	AEC-Q200 Test 15 MIL-STD-202 Method 210	260 ±5 °C for 10 ±1 sec	< ±0.5 %
Solderability	AEC-Q200 Test 18 J-STD-002	Solder dipping at 235 ±3 °C, 3 ±0.5 sec. Pre-condition: Aging 4 hours at 155 °C dry heat	At least 95 % of surface area of electrode shall be covered with new solder
High Temperature Exposure	AEC-Q200 Test 3 MIL-STD-202 Method 108	170 °C, 1000 hrs	< ±1 %
Resistance to Solvents	AEC-Q200 Test12 MIL-STD-202 Method 215	a: Isopropyl Alcohol c: Deionized Water b: Terpene Defluxer	< ±1 %
Board Flex	AEC-Q200-005	Bending width 2 mm for 60 sec.	< ±0.5 %
Insulation Resistance	IEC 60115-1-4.6 JIS-C5201-4.6	100 VDC for 1 minute	>100 MΩ
Vibration	AEC-Q200 Test 14 MIL-STD-202 Method 204	5 g's for 20 mins., 12 cycles 10~2000 Hz	< ±0.5 %
Terminal Strength/Shear	AEC-Q200-006	1.8 kg for 60 sec.	< ±1 %
ESD	AEC-Q200-002	Apply 500 V	< ±1 %
Mechanical Shock	AEC-Q200 Test 13 MIL-STD-202 Method 213	100 g's for 6 ms	< ±0.5 %
Flammability	AEC-Q200 Test 20 UL-94	V-0 or V-1 are acceptable. Electrical test not required	V-0


Rated Voltage

The rated voltage is calculated by the following formula:


$$V = \sqrt{P \times R}$$

V: Rated Voltage (V)
P: Rated Power (W)
R: Resistance Value (Ω)

Derating Curve



Construction




Specifications are subject to change without notice. Users should verify actual device performance in their specific applications. The products described herein and this document are subject to specific legal disclaimers as set forth on the last page of this document, and at www.bourns.com/docs/legal/disclaimer.pdf.

CRK Series Metal Strip, Wide Terminal Current Sense Resistor



Solder Reflow Recommendations



Solder Profile	Lead Free Assembly
Average ramp-up rate (T _{smax} to T _p)	3 °C / second max.
Preheat: - Temperature Min. (T _{smin}) - Temperature Max. (T _{smax}) - Time (T _{smin} to T _{smax}) (t _s)	150 °C 200 °C 60~150 seconds
Time maintained above: - Temperature (T _L) - Time (T _L)	217 °C 60~120 seconds
Peak Temperature (T _p)	260 °C
Time within +0/-5 °C of actual Peak Temperature (T _p) ²	10 seconds
Ramp-down Rate	6 °C / second max.
Time 25 °C to Peak Temperature	8 minutes max.

How to Order

CRK 0612 - F Z - R005 E

Model _____
 CRK = Metal Strip, Wide Terminal Current Sense Resistor

Size _____
 0612 = 0612 Size 1225 = 1225 Size
 0815 = 0815 Size

Resistance Tolerance _____
 F = ±1 %
 J = ±5 %

TCR _____
 Z = ±100 PPM/°C

Resistance Code – (See Standard Resistance Values Table) _____
 “R” (decimal point) followed by three significant digits
 (example: R004 = 0.0040 ohms)

Packaging _____
 E = Tape and Reel
 CRK0612: 5,000 pcs. / 7-inch reel;
 CRK0815: 4,000 pcs. / 7-inch reel
 CRK1225: 4,000 pcs. / 7-inch reel

Popular Resistance Values

CRK0612

Code	R Value
R001	1 mΩ
R003	3 mΩ
R005	5 mΩ

CRK0815

Code	R Value
R003	3 mΩ
R004	4 mΩ
R005	5 mΩ
R010	10 mΩ

CRK1225


Code	R Value	Code	R Value
R001	1 mΩ	R009	9 mΩ
R002	2 mΩ	R010	10 mΩ
2L20	2.2 mΩ	R012	12 mΩ
R003	3 mΩ	R015	15 mΩ
R004	4 mΩ	R020	20 mΩ
R005	5 mΩ	R025	25 mΩ
R006	6 mΩ	R030	30 mΩ
R007	7 mΩ	R033	33 mΩ
R008	8 mΩ	R040	40 mΩ

Specifications are subject to change without notice.
 Users should verify actual device performance in their specific applications.
 The products described herein and this document are subject to specific legal disclaimers as set forth on the last page of this document, and at www.bourns.com/docs/legal/disclaimer.pdf.

CRK Series Metal Strip, Wide Terminal Current Sense Resistor




Packaging Dimensions (Conforms to EIA RS-481A)



Model	A	B	W	F	E	P ₁	P ₂	P ₀	D ₀	T	K
CRK0612 (paper tape)	2.00 ± 0.15 (.079 ± .006)	3.60 ± 0.20 (.142 ± .008)	8.00 ± 0.20 (.315 ± .008)	3.50 ± 0.05 (.138 ± .002)					$1.50 +0.1/-0$ (.059 +.004/-0)	0.84 ± 0.10 (.033 ± .004)	—
CRK0815 (embossed)	2.60 ± 0.20 (.102 ± .008)	4.50 ± 0.20 (.177 ± .008)	12.00 ± 0.20 (.472 ± .008)	5.50 ± 0.05 (.217 ± .002)	1.75 ± 0.10 (.069 ± .004)	4.00 ± 0.10 (.157 ± .004)	2.00 ± 0.10 (.079 ± .004)	4.00 ± 0.10 (.157 ± .004)		0.30 ± 0.10 (.012 ± .004)	1.10 ± 0.10 (.043 ± .004)
CRK1225 (embossed)	3.60 ± 0.20 (.142 ± .008)	6.90 ± 0.20 (.272 ± .008)	12.00 ± 0.20 (.472 ± .008)	5.50 ± 0.05 (.217 ± .002)					2.00 ± 0.10 (.080 ± .004)	0.30 ± 0.10 (.012 ± .004)	1.20 ± 0.15 (.047 ± .006)

DIMENSIONS: $\frac{\text{MM}}{\text{INCHES}}$



Americas: Tel: +1 951-781-5500 • Email: americus@bourns.com
 Mexico: Tel: +52-614-478-0400 • Email: mexicus@bourns.com
 Asia: Tel: +886-2-2562-4117 • Email: asiacus@bourns.com
 EMEA: Tel: +36 88 885 877 • Email: eurocus@bourns.com
www.bourns.com

REV. 06/25

Specifications are subject to change without notice.
 Users should verify actual device performance in their specific applications.
 The products described herein and this document are subject to specific legal disclaimers as set forth on the last page of this document, and at www.bourns.com/docs/legal/disclaimer.pdf.

This legal disclaimer applies to purchasers and users of Bourns® products manufactured by or on behalf of Bourns, Inc. and its affiliates (collectively, "Bourns").

Unless otherwise expressly indicated in writing, Bourns® products and data sheets relating thereto are subject to change without notice. Users should check for and obtain the latest relevant information and verify that such information is current and complete before placing orders for Bourns® products.

The characteristics and parameters of a Bourns® product set forth in its data sheet are based on laboratory conditions, and statements regarding the suitability of products for certain "typical" applications are based on Bourns' knowledge of typical requirements in generic applications. Bourns assumes that "typical" applications include failsafe/backup features to address critical risks to users and are designed to allow rework of Bourns® product to avoid scrap of a device solely due to malfunctioning Bourns® product. The characteristics and parameters of a Bourns® product in a user application may vary from the data sheet characteristics and parameters due to (i) the combination of the Bourns® product with other components in the user's application, or (ii) the environment of the user application itself. The characteristics and parameters of a Bourns® product also can and do vary in different applications and actual performance may vary over time. Thus, users should always verify the actual performance of the Bourns® product in their specific devices and applications and make their own independent judgments regarding the suitability of Bourns® product and the amount of additional test margin to design into their device or application to compensate for differences between laboratory and real-world conditions.

Unless Bourns has explicitly designated an individual Bourns® product as meeting the requirements of a particular industry standard (e.g., IATF 16949) or a particular qualification (e.g., UL listed or recognized), Bourns is not responsible for any failure of an individual Bourns® product to meet the requirements of such industry standard or particular qualification even if such industry standard or qualification is a "state of art". Users of Bourns® products are responsible for ensuring compliance with safety-related requirements and standards applicable to their devices or applications.

Bourns® products are not recommended, authorized or intended for use in applications where failure or malfunction may result in personal injury, death, or severe property or environmental damage, such as without limitation nuclear, life-critical medical and certain automotive and aviation applications. Except as set forth in the bullet points below or unless expressly and specifically approved in writing on a case-by-case basis by an authorized Bourns' representative, use of any Bourns® products in such unauthorized high-risk applications is at the user's sole risk.

- Bourns considers implantable/invasive devices and devices/procedures designed as life-supporting or life-sustaining by the U.S. Food and Drug Administration or equivalent organizations outside of the United States as "life-critical" medical applications. Bourns expressly identifies those Bourns® standard products that are suitable for use in typical medical applications that are not life-critical in its publication entitled "Bourns Medical Grade Component Guide."
- Bourns expressly identifies those Bourns® standard products that are suitable for use in typical automotive applications associated with any Automate Safety Integrity Level (ASIL) in its publication entitled "Bourns Automotive Grade Component Guide." Bourns' designation of Bourns® product as compliant with the AEC-Q standard does not by itself mean that Bourns has approved such product for use in an automotive application.
- Bourns expressly identifies Bourns® standard products that are suitable for use in the typical aviation applications/systems requiring System Design Assurance Level (RTCA DO-254 DAL) of C, D or E in its publication entitled "Bourns Civilian Aerospace/Aviation Grade Component Guide." Bourns does not test its products for compliance with United States Federal Aviation Administration standards or any other generally equivalent governmental organization standard applicable to products designed or manufactured for use in aviation applications. Use of Bourns® standard components in aviation applications associated with RTCA DO-254 DAL A or B without proper approval noted above shall be at the user's sole risk.
- Bourns will review and authorize on a case-by-case basis the use of Bourns® standard products which are at least AEC-Q compliant in space-related civil applications (rockets, satellites) with a negotiated cross-waiver and indemnity agreement.

The use and level of testing applicable to Bourns® custom products shall be negotiated on a case-by-case basis by Bourns and the user for which such Bourns® custom products are specially designed. Absent a written agreement between Bourns and the user regarding the use and level of such testing, the above provisions applicable to Bourns® standard products shall also apply to such Bourns® custom products.

Use of Bourns® products or Bourns' technology in military/defense applications must be reviewed with Bourns for compliance with applicable export control laws and embargoes. Users shall not sell, transfer, export or re-export (which includes transfers within a country) any Bourns® products or technology or technical data for use in activities which involve the design, development, production, use or stockpiling of nuclear, chemical or biological weapons or missiles, nor shall they use Bourns® products or technology or technical data in any facility which engages in activities relating to such devices. Further, Bourns® products and Bourns' technology and technical data may not under any circumstance be exported or re-exported to countries subject to international sanctions or embargoes. Bourns® products and technology may not, without prior authorization from Bourns and/or the Government of a country where such product/technology is designed and/or manufactured, be resold, transferred, or re-exported (including within the same country) to any party not eligible to receive commodities, software, and technical data originating in such country.

To the maximum extent permitted by applicable law, Bourns disclaims (i) any and all liability for special, punitive, consequential, incidental or indirect damages or lost revenues or lost profits, and (ii) any and all implied warranties (those not based on parameters specified in Bourns' data sheets and/or specifications), including implied warranties of fitness for particular purpose, non-infringement and merchantability.

For your convenience, copies of this Legal Disclaimer Notice with German, Spanish, Japanese, Traditional Chinese and Simplified Chinese bilingual versions are available at:

Web Page: <https://www.bourns.com/legal/disclaimers-terms-and-policies>

PDF: <https://www.bourns.com/docs/Legal/disclaimer.pdf>